

Specifications

■ Bulb

Headlight	LED
Brake light/Taillight	LED
Position light	LED
Front turn signal light/ Position light	LED
Rear turn signal light	LED
License plate light	LED

■ Fuse

Main fuse	30 A
Other fuse	30 A, 15 A, 10 A, 7.5 A

■ Torque Specifications

Engine oil drain bolt	22 lbf-ft (30 N·m, 3.1 kgf-m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf-m)
Bearing holder pinch bolt	20 lbf-ft (27 N·m, 2.8 kgf-m)
Front wheel axle bolt	58 lbf-ft (79 N·m, 8.1 kgf-m)
Front wheel brake caliper mounting bolt	33 lbf-ft (45 N·m, 4.6 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf-m)
Muffler mount bolt and nut	16 lbf-ft (22 N·m, 2.2 kgf-m)
Right step bracket bolt A	27 lbf-ft (37 N·m, 3.8 kgf-m)
Right step bracket bolt B	27 lbf-ft (37 N·m, 3.8 kgf-m)
Muffler band bolt	16 lbf-ft (22 N·m, 2.2 kgf-m)
Rear wheel nut	80 lbf-ft (108 N·m, 11.0 kgf-m)