

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
Engine oil capacity	After draining	3.0 US qt (2.8 liters)
	After draining & filter change	3.2 US qt (3.0 liters)
	After disassembly	3.9 US qt (3.7 liters)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	3.2 US qt (3.0 liters)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain lube or equivalent	
Drive chain slack	1 to 1 3/8 in (25 to 35 mm)	
Standard drive chain	DID 50VA11 or RK 50HFOZ6	
	No. of links	116
Standard sprocket sizes	Front sprocket	16T
	Rear wheel sprocket	42T

## ■ Bulbs

Headlight	12V-55W × 2
Brake light	LED
Taillight	LED
Front turn signal lights	12V-21W × 2
Rear turn signal lights	12V-21W × 2
Position light	LED
License plate light	12V-5W

## ■ Fuses

Main fuse	30A	
Other fuses	<b>CBR1000RR/S</b>	20A, 10A
	<b>CBR1000RA</b>	30A, 20A, 10A