

Specifications

■ Service Data

Tyre size	Front	110/70-17M/C 54S
	Rear	140/70-17M/C 66S
Tyre type	Bias-ply, tubeless	
	Recommended tyre	IRC RX-01FD IRC RX-01RZD
Tyre air pressure (Driver only)	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
	Rear	200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure (Driver and passenger)	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plug	(standard)	SILMAR9C9 (NGK)
Spark plug gap	(non-adjustable)	0.80 - 0.90 mm (0.031 - 0.035 in)
	Idle speed	1,500 ± 100 rpm
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	1.9 L (2.0 US qt, 1.7 Imp qt)
	After draining & engine oil filter change	2.1 L (2.2 US qt, 1.8 Imp qt)
	After disassembly	2.4 L (2.5 US qt, 2.1 Imp qt)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	0.80 L (0.85 US qt, 0.70 Imp qt)	
Recommended coolant	HONDA PRE-MIX COOLANT	
Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains. If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	25 - 35 mm (1.0 - 1.4 in)	
Standard drive chain	DID520VF	
	No. of links	112
Standard sprocket size	Drive sprocket	14T
	Driven sprocket	41T