





| Items | | Frequency *1 | | | | | | | | Regular Replace | Refer to page | |
|----------------------------|------------------------|---|-----|----------|----------|----------|----------|----------|----------|-----------------|---------------|----|
| | | × 1,000 mi | 0.6 | 4 | 8 | 12 | 16 | 20 | 24 | | | |
| | | × 1,000 km | 1.0 | 6.4 | 12.8 | 19.2 | 25.6 | 32.0 | 38.4 | | | |
| Non-Emission-Related Items | Drive Chain | Every 600 mi (1,000 km): I L | | | | | | | | | 76 | |
| | Brake Fluid *5 | | | I | I | I | I | I | I | 2 Years | 72 | |
| | Brake Pads Wear | | | I | I | I | I | I | I | | 73 | |
| | Brake System | | | | I | | I | | I | | 72 | |
| | Brake Light Switch | | | | I | | I | | I | | 74 | |
| | Headlight Aim | | | | I | | I | | I | | 85 | |
| | Clutch System | | | I | I | I | I | I | I | | 80 | |
| | Side Stand | | | | I | | I | | I | | 75 | |
| | Suspension |  | | | | I | | I | | I | | - |
| | Nuts, Bolts, Fasteners |  | | | | I | | I | | I | | - |
| | Wheels/Tires |  | | | | I | | I | | I | | 56 |
| | Steering Head Bearings |  | | | | I | | I | | I | | - |

Notes:

- *1: At higher odometer readings, repeat at the frequency interval established here.
- *2: Service more frequently when riding in unusually wet or dusty areas.
- *3: Service more frequently when riding in rain or at full throttle.
- *4: 50 STATE (meets California).
- *5: Replacement requires mechanical skill.