

Service Data

Tyre size	Front	100/80-17M/C 52P
	Rear	130/70-17M/C 62P
Tyre type	Bias-ply, tubeless	
Recommended tyre	Front	IRC RX-01F
	Rear	IRC RX-01R
Tyre air pressure (Driver only)	Front	175 kPa (1.75 kgf/cm ² , 25 psi)
	Rear	200 kPa (2.00 kgf/cm ² , 29 psi)
Tyre air pressure (Driver and passenger)	Front	175 kPa (1.75 kgf/cm ² , 25 psi)
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plug	(standard)	MR9C-9N (NGK) or U27EPR-N9 (DENSO)
Spark plug gap	0.8 - 0.9 mm (0.03 - 0.04 in)	
Idle speed	1,600 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SJ or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	
	After draining	1.1 L (1.2 US qt, 1.0 Imp qt)
Engine oil capacity	After disassembly	1.3 L (1.4 US qt, 1.1 Imp qt)

Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	0.58 L (0.61 US qt, 0.51 Imp qt)	
Recommended coolant	HONDA PRE-MIX COOLANT	
Recommended drive chain lubricant	Drive chain lubricant.	
	If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	25 - 35 mm (1.0 - 1.4 in)	
Standard drive chain	FSCM428H or RK428HSE1	
	No. of links	128
Standard sprocket size	Drive sprocket	15T
	Driven sprocket	45T