

GL1800/B

■ Main Components

Overall length	GL1800	101.4 in (2,575 mm)
	GL1800B	97.4 in (2,475 mm)
Overall width	36.4 in (925 mm)	
Overall height	GL1800	56.3 in (1,430 mm)
	GL1800B	52.8 in (1,340 mm)
Wheelbase	66.7 in (1,695 mm)	
Minimum ground clearance	5.1 in (130 mm)	
Caster angle	30.5°	
Trail	4.3 in (109 mm)	
Curb weight	GL1800 USA model	836 lb (379 kg)
	GL1800 Canada model	838 lb (380 kg)
	GL1800B USA model	787 lb (357 kg)
	GL1800B Canada model	805 lb (365 kg)
Maximum weight capacity*1	GL1800	423 lb (192 kg)
	GL1800B	421 lb (191kg)
Maximum luggage weight	Travel trunk (Except GL1800B)	20.0 lb (9.0 kg)
	Each saddlebag	20.0 lb (9.0 kg)
	Fairing pocket	4.5 lb (2.0 kg)
	Shelter case	6.6 lb (3.0 kg)
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	11.2 ft (3.4 m)	

*1 Including rider, all luggage, and accessories

Displacement	111.8 cu-in (1,833 cm ³)	
Bore x stroke	2.87 x 2.87 in (73.0 x 73.0 mm)	
Compression ratio	10.5:1	
Fuel	Unleaded gasoline Recommended: 86 PON or higher	
Tank capacity	5.5 US gal (21 liters)	
Battery	GYZZ20L	
	12 V-20 Ah (10 HR)	
Gear ratio	1st	2.200
	2nd	1.416
	3rd	1.035
	4th	0.820
	5th	0.666
	6th	0.521
Reduction ratio (primary / secondary / final)	1.795 / 0.972 / 2.615	

■ Service Data

Tire size	Front	130/70R18M/C 63H
	Rear	200/55R16M/C 77H
Tire type	Radial, tubeless	
Recommended Tire	Front	BRIDGESTONE G853 RADIAL G DUNLOP D423F
	Rear	BRIDGESTONE G852 RADIAL G DUNLOP D423
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm ²)
	Rear	41 psi (280 kPa, 2.80 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	CR6HSB-9 (NGK)
Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	(non-adjustable)	730 ± 100 rpm
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	3.7 US qt (3.5 liters)
Engine oil capacity	After draining & engine oil filter change	3.9 US qt (3.7 liters)
	After disassembly	4.6 US qt (4.4 liters)