

Specifications

Service Data

Tyre size	Front	70/90-17M/C 38P
	Rear	80/90-17M/C 50P
Tyre type	NBC110MDF/KDF	Bias-ply, tube
	NBC110MCD	Bias-ply, tubeless
Recommended Tyre	NBC110MDF/KDF	IRC NF63B Z Vee Rubber V357F CHENG SHIN C-6016 YUANXING CORDIAL P180
	NBC110MCD	DUNLOP TT100
Tyre air pressure	Front	200 kPa (2.00 kgf/cm ² , 29 psi) [Driver only]
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi) [Driver and 1 passenger] 280 kPa (2.80 kgf/cm ² , 41 psi)
Spark plug	(standard)	CPR6EA-9S (NGK) or U20EPR9S (DENSO)
Spark plug gap		0.8 to 0.9 mm (0.03 to 0.04 in)

Idle speed (non-adjustable)	1,400 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," or "Resource Conserving" SAE 10W-30, JASO T 903 standard MA	
Engine oil capacity	After draining 0.8 litres (0.8 US qt, 0.7 Imp qt)	
	After disassembly 1.0 litres (1.1 US qt, 0.9 Imp qt)	
Recommended drive chain lubricant	Drive chain lubricant. If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	20 to 30 mm (0.8 to 1.2 in)	
Standard drive chain	DID420AD or KMC420JB or RK420SL	
	No. of links	102
Standard sprocket size	Front sprocket	14T
	Rear wheel sprocket	37T

Specifications