

■ Bulbs

Headlight	12 V-60/55 W
Brake light/Taillight	LED
Front turn signal light	12 V-21/5 W × 2
Rear turn signal light	12 V-21 W × 2
License plate light	12 V-5 W

■ Fuses

Main fuse	30 A	
Other fuse	VT1300CX	20 A, 10 A
	VT1300CXA	30 A, 20 A, 10 A

■ Torque Specifications

Seat mounting bolts B	16 lbf-ft (22 N·m, 2.2 kgf-m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf-m)
Engine oil drain bolt	22 lbf-ft (30 N·m, 3.1 kgf-m)
Air cleaner housing cover bolt	1.1 lbf-ft (1.5 N·m, 0.2 kgf-m)
Final drive oil fill hole cap	9 lbf-ft (12 N·m, 1.2 kgf-m)
Final drive oil drain bolt	9 lbf-ft (12 N·m, 1.2 kgf-m)
Headlight bolt and nut	7 lbf-ft (10 N·m, 1.0 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf-m)
Front wheel axle bolt	47 lbf-ft (64 N·m, 6.5 kgf-m)
Front wheel caliper fixing bolt	23 lbf-ft (31 N·m, 3.2 kgf-m)
Rear brake bracket bolt	51 lbf-ft (69 N·m, 7.0 kgf-m)
Rear wheel axle nut	94 lbf-ft (127 N·m, 13.0 kgf-m)
Rear wheel axle holding bolt	20 lbf-ft (27 N·m, 2.8 kgf-m)
Exhaust pipe joint nut	17 lbf-ft (23 N·m, 2.3 kgf-m)
Muffler bracket bolt A, B, and nut	20 lbf-ft (27 N·m, 2.8 kgf-m)